

AMENDMENTS TO THE CLAIMS

Please find below a complete listing of the claims in the application, including their status as effected by the present amendment:

1. *(currently amended)* A device for integration into a base station of a type that includes at least one radio-transceiver for receiving and transmitting radio communications to a plurality of subscriber stations; the device ~~[[use in a wireless communication system]]~~ comprising:

an input device operable to be coupled to the at least one radio-transceiver for receiving a handoff signal from the at least one radio-transceiver at a first mode respective to a first coverage area of the communication system;

an output device for delivering the handoff signal at a second mode respective to a second coverage area;

a converter coupled to said input device and said output device for translating the handoff signal from the first mode into the second mode; the second mode handoff signal for indicating to a subscriber station operating in the second mode within both of the coverage areas to switch from the second mode to the first mode so that the subscriber station operates in the first mode ~~[[coverage area]]~~.

2. *(currently amended)* The device according to claim 1 wherein said first coverage area and said second coverage area of said system are each based on a respective protocol selected from the group consisting of CDMA, TDMA, GSM, GPRS, AMPS and FDMA.

3. *(previously presented)* The device according to claim 2 wherein said protocols respective to said coverage areas are different.

4. *(previously presented)* The device according to claim 1 wherein said handoff signal is a conventional CDMA re-direction signal, and wherein said first mode is a first frequency and said second mode is a second frequency different from said first frequency.

5. *(original)* The device according to claim 4 wherein said first coverage area and said second coverage area are served by respective CDMA base stations.

6. *(previously presented)* The device according to claim 1 wherein said output device is operable to transmit said handoff signal to a base station power combiner for delivering said converted handoff signal to a base station antenna for outputting said handoff signal.

7. *(currently amended)* The device according to claim 4 wherein said converter comprises a down-converter operable to receive said handoff signal from said input device and for converting said handoff signal ~~[[trigger]]~~ from said first frequency to an intermediate frequency and an up-converter for converting said intermediate frequency to said second frequency.

8. *(original)* The device according to claim 7 further comprising a microcontroller operably connected to said down-converter and said up-converter such that said first frequency and said second frequency is user-selectable.

9. *(previously presented)* The device according to claim 8 wherein said microcontroller is further operable to perform at least one of logging various conversions performed by said converter, and generating alarms upon occurrence of a pre-determined event.

10. *(currently amended)* A method for generating a handoff signal at a base station of a type that includes at least one radio-transceiver for receiving and transmitting radio communications with respect to a plurality of subscriber stations, the method comprising:

receiving a handoff signal from the at least one radio-transceiver at a first mode respective to a first coverage area;

converting said handoff signal from said first mode to a second mode respective to a second coverage area; and,

outputting said handoff signal into said second coverage area.

11. *(currently amended)* The method according to claim 10 wherein said first coverage area and said second coverage area are each based on a respective protocol selected from the group consisting of CDMA, TDMA, GSM, GPRS, AMPS and FDMA.

12. *(original)* The method according to claim 11 wherein said protocols respective to said coverage areas are different.

13. *(previously presented)* The method according to claim 10 wherein said handoff signal is a conventional CDMA re-direction signal, and wherein said first mode is a first frequency and said second mode is a second frequency different from said first frequency.

14. *(original)* The method according to claim 13 wherein said first coverage area and said second coverage area are served by respective CDMA base stations.

15. *(previously presented)* The method according to claim 10 wherein outputting of said handoff signal comprises transmitting said handoff signal to a base station power combiner for delivering said converted handoff signal to a base station antenna for outputting said handoff signal into said second coverage area.

16. *(previously presented)* The method according to claim 13 further comprising receiving an input signal identifying at least one said frequencies for use in performing a [[the]] remainder of the steps.

17. *(previously presented)* A system for performing handoff comprising:

a first base station operating at a first mode and comprising at least one radio-transceiver for receiving and transmitting radio communications to a plurality of subscriber stations; said at least one radio-transceiver operable to generate a handoff signal at said first mode;

a second base station operating a second mode;

a handoff device including an input device for receiving said handoff signal from said at least one radio-transceiver at said first mode; an output device for delivering said handoff signal at said second mode in a coverage area respective to said second base station; a converter coupled to said input device and said output device for translating the handoff signal from the first mode into the second mode; the second mode handoff signal for indicating to a subscriber station operating in the second mode within both of the coverage areas to switch from the second mode to the first mode.

18. *(original)* The system according to claim 17 wherein said first base station and said second base station of said system are based on a protocol selected from the group consisting of CDMA, TDMA, GSM, GPRS, AMPS and FDMA.

19. *(original)* The system according to claim 18 wherein said protocols respective to said coverage areas are different.

20. *(previously presented)* The system according to claim 17 wherein said handoff signal is a conventional CDMA re-direction signal, and wherein said first mode is a first frequency and said second mode is a second frequency different from said first frequency.

21. *(previously presented)* The system according to claim 17 wherein said first base station further comprises a base station power combiner and a base station antenna coupled to said base station power combiner for transmitting radio communications to

a plurality of subscriber stations; said output device further operable to transmit said handoff signal to said base station power combiner.

22. *(currently amended)* The system according to claim 20 wherein said converter comprises a down-converter operable to receive said handoff signal from said input device and for converting said handoff signal ~~[[trigger]]~~ from said first frequency to an intermediate frequency and an up-converter for converting said intermediate frequency to said second frequency.

23. *(original)* The system according to claim 22 further comprising a microcontroller operably connected to said down-converter and said up-converter such that said first frequency and said second frequency is user-selectable.

24. *(original)* The system according to claim 23 wherein said microcontroller is further operable to perform at least one of logging various conversions performed by said converter, and generating alarms if said converter operates outside of desired specifications.

25. *(cancelled)*

26. *(cancelled)*

27. *(currently amended)* A device for use in a wireless communication system comprising:

an input device coupled to a base-station radio-transceiver for receiving a handoff signal from said base-station radio-transceiver at a first mode respective to a first coverage area of the communication system;

an output device for delivering the handoff signal at at least one additional mode respective to at least one additional coverage area;

a converter for translating the handoff signal from the first mode into the at least one additional mode; the ~~[[additional-mode]]~~ handoff signal for each of

the at least one additional mode indicating to a subscriber station operating at ~~[[in]]~~ the respective additional mode within the respective coverage area~~[[s]]~~ to switch from the respective additional mode to the first mode so that the subscriber station operates in the first mode ~~[[coverage area]]~~.

28. *(cancelled)*

29. *(cancelled)*

30. *(currently amended)* A base station for use in a wireless communication system comprising:

a radio-transceiver for receiving and transmitting radio communications with respect to a plurality of subscriber stations ~~[[;]]~~ ;

data-processing equipment for carrying at least a portion of said communications over a backhaul ~~[[;]]~~ ; and

~~[[said base station further including]]~~ a device for performing handoff comprising an input device for receiving a handoff signal from said radio-transceiver ~~[[signal]]~~ at a first mode respective to a first coverage area of the communication system; an output device for delivering the handoff signal at a second mode respective to a second coverage area; a converter coupled to said input device and said output device for translating the handoff signal from the first mode into the second mode; the second mode handoff signal for indicating to a subscriber station operating in the second mode within both of the coverage areas to switch from the second mode to the first mode so that the subscriber station operates in the first mode ~~[[coverage area]]~~.

31. *(original)* The base station according to claim 30 wherein said base station is based on the CDMA protocol.

32. *(currently amended)* The base station according to claim 30 wherein the radio-transceiver is operable to receive and transmit radio communications with respect to the plurality of subscriber stations in the first mode.

33. *(cancelled)*

34. *(currently amended)* A handoff device for use in a wireless CDMA communication system and operable to be coupled to a radio-transceiver of a base station, the handoff device comprising an input device for receiving a CDMA re-direction signal from the radio-transceiver at a first frequency respective to a first coverage area of said communication system; a first converter connected to said input device for converting said CDMA re-direction signal from said first frequency to an intermediate frequency; a second converter connected to said first converter for converting said CDMA re-direction signal from said intermediate frequency to a second frequency; an output device connected to said second converter for delivering said CDMA re-direction signal at said second frequency within a second coverage area; said CDMA re-directional signal for indicating to a subscriber station operating in said second frequency and within both of said coverage areas to switch from said second frequency to said first frequency ~~[[so that said subscriber station operates in said first coverage area]]~~.

35. *(previously presented)* A base station that incorporates the device according to claim 1.

36. *(previously presented)* The base station according to claim 35 wherein the base station further comprises a base station power combiner and a base station antenna coupled to said base station power combiner for transmitting radio communications to a plurality of subscriber stations; said output device further operable to transmit said handoff signal to said base station power combiner.

37. *(currently amended)* The base station according to claim 35 wherein said first coverage area and said second coverage area of said system are each based on a

respective protocol selected from the group consisting of CDMA, TDMA, GSM, GPRS, AMPS and FDMA.

38. *(previously presented)* The base station according to claim 37 wherein said protocols respective to said coverage areas are different.

39. *(currently amended)* The base station according to claim 35 wherein said handoff signal is a conventional CDMA re-direction signal ~~[[, and wherein said first mode is a first frequency and said second mode is a second frequency different from said first frequency]]~~.

40. *(currently amended)* The base station according to claim 39 wherein said base station is a first CDMA base station and said second coverage area is served by a second CDMA base station different from said first CDMA base station.